



**Over 100 Years of Experience**

## Butyl Caulking Tape

A non-skinning, non-drying sealant of butyl-polyiso-butylene base extruded compound with excellent physical and weathering characteristics. Retains adhesion and elasticity in weather extremes (-60 to 212°F) for prolonged periods. Excludes air, dust, ice, and water. Ideal for sealing laps on all types of sheeting.

Feet Size	Feet Per Roll	Rolls Per Box	Feet Per Box
3/32" x 3/8"	45	48	2,160
3/32" x 1/2"	40	40	1,600
1/8" x 1/2"	40	35	1,400
1/8" x 3/4"	40	35	1,400
1/8 x 2"	30	8	240

Note: Other sizes are available.

All test results and recommendations are based on laboratory tests. Specific job site conditions should be taken into consideration when specifying the proper fastener.

Because applications vary, we assume no liability for use of this information.



**[www.atlasfasteners.com](http://www.atlasfasteners.com)**

1628 Troy Road • Ashland Ohio, 44805  
T: 419-289-6171 • F: 419-289-2564

**800-321-6977**

### SALES AND SERVICE CENTERS

**Ashland, Ohio**  
1-800-321-6977

**Flat Rock, NC**  
1-800-364-0370

**Houston, TX**  
1-800-503-2105

**Salem, OR**  
1-800-547-8740