



Over 100 Years of Experience

EnduraFast ACQ Lumber Fastener

Won't Rust in ACQ Treated Wood

Easy Installation

- High hex head design provides for positive socket fit and stability during installation
- Magnetic 410 stainless stays in the socket
- Coarse thread pitch provides fast penetration

Painted Head

- Stocked in standard panel colors

Sizes

- Available in lengths of 1", 1-1/2" and 2"

Convenience

- Conveniently bagged at 100 pieces per
- Clearly marked for use in treated lumber
- Black Coating
- Makes the ACQ fastener easy to identify
- Provides additional corrosion resistance



- Diameter: #10
- Threads per In.: 14
- Length: 1", 1 1/2", 2"
- Point: Sharp
- Material: 410 Stainless Steel
- Coating: Mech. Zinc w/Black Coating

Engineering Test Report

Fastener Diameter	Minimum Torsional	Minimum Tensile	Minimum Shear
#10	68 in. lbs.	1817 lbs.	1216 lbs.

Pull Out Values



TEST MATERIAL	PENETRATION	RESULTS
S-P-F #2	1"	498
S-P-F #2	1-1/2"	899
Hem Fir #2	1"	694
Hem Fir #2	1-1/2"	1080
1/2 CDX	FULL	361
5/8 CDX	FULL	490
3/4 CDX	FULL	560

Note: Pull-out values are a measurement of wood material strength. Actual field values may vary.



www.atlasfasteners.com

1628 Troy Road • Ashland Ohio, 44805
T: 419-289-6171 • F: 419-289-2564

800-321-6977

SALES AND SERVICE CENTERS

Ashland, Ohio
1-800-321-6977

Flat Rock, NC
1-800-364-0370

Houston, TX
1-800-503-2105

Salem, OR
1-800-547-8740