



Dektite Original

The original
watertight flashing
for metal roof
penetrations



- Easy to Identify**
Dektite brand name engraved on product for traceability
- Unique Cone Design**
Provides 10mm (1/2") continuous contact with flashed pipe providing a watertight seal
- Clear Markings**
Makes for easier cutting to pipe size
- Proven design**
Associated with the roofing industry globally for over 40 years
- Size ranges - Numbers 0-9**
Available in Black and Grey EPDM, and red silicone
- Twenty year warranty**
Just fit it and forget it - we've got you covered

Selection Guide

Black EPDM	Product Code		Description	Pipe OD	Base OD	Roof Pitch	Carton Qty
	Grey EPDM	Red Silicone					
DF100B	DF100G	DF200RE	Dektite Original #0	0 - 1.5	3.75	¹² / ₁₂	40
DF101B	DF101G	DF201RE	Dektite Original #1	0.25 - 2.5	4.75	¹⁰ / ₁₂	10
DF102B	DF102G	DF202RE	Dektite Original #2	1.75 - 3.75	6.5	¹⁰ / ₁₂	10
DF103B	DF103G	DF203RE	Dektite Original #3	0.25 - 5	8	¹⁰ / ₁₂	10
DF104B	DF104G	DF204RE	Dektite Original #4	3 - 6.25	9.5	¹⁰ / ₁₂	10
DF105B	DF105G	DF205RE	Dektite Original #5	4.25 - 7.5	11	¹⁰ / ₁₂	5
DF106B	DF106G	DF206RE	Dektite Original #6	5 - 9	12.75	¹⁰ / ₁₂	5
DF107B	DF107G	DF207RE	Dektite Original #7	6 - 11	14.75	¹⁰ / ₁₂	5
DF108B	DF108G	DF208RE	Dektite Original #8	7 - 13	16.75	¹⁰ / ₁₂	5
DF109B	DF109G	DF209RE	Dektite Original #9	10 - 19	25.5	¹⁰ / ₁₂	1

Available in Black and Grey EPDM or Red Silicone.

EPDM will withstand constant temperatures at the roofline of -58°F to 239°F and up to 302°F intermittently.

Red Silicone will withstand constant temperatures at the roofline of -58°F to 392°F and up to 482°F intermittently.

Please Note that the outside temperature of the pipe may be significantly different to the exit temperature of the appliance.

Installation Information



1

Cut Dektite at appropriate pipe diameter marking.



2

Slide Dektite flashing down over pipe.



3

Apply sealant on underside of flexible aluminum base.



4

Press Dektite base into contours of panel configuration.



5

Fasten Dektite to surface with long-life, self-drilling fasteners. Apply additional sealant around base if desired.

- Always use the neutral cure low modulus silicone for sealing
- In corrosive and coastal environments, fix using blind aluminum rivets

Dektite Retrofit



Dektite Original



Need to flash a tiled roof? Contact DEKS to discuss the tile roof flashing range.