

# ATLAS

## BUILDING PRODUCTS

A MARMON BERKSHIRE HATHAWAY COMPANY

### PRODUCT SPECIFICATION SHEET

---

### LONG LIFE #12 WOOD ULTIMATE®



#### ASHLAND OHIO

1628 TROY ROAD  
ASHLAND, OH 44805  
(800) 321-6977

#### FLAT ROCK NORTH CAROLINA

161 COMMERCIAL BLVD  
FLAT ROCK, NC 28731  
(828) 692-2603

#### HOUSTON TEXAS

4822 N. SAM HOUSTON PKWY W  
SUITE 100  
HOUSTON, TX 77086  
(800) 503-2105

#### SALEM OREGON

2655 TURNER ROAD  
SALEM, OR 97302  
(503) 362-1373

## LONG LIFE #12 WOOD ULTIMATE®

**Head**

5/16" hex head

Low profile design where fastener blends with the panel

Zinc cast head for long life performance

**Thread**

Threads per inch: 11

**Point**

26 degree sharp point for quick piercing

**Washer**

EPDM tubular washer

**Material**

Carbon steel shank

**Finish**

Mechanical zinc plated shank with die cast head warranted against red rust for the life of the building

SIZE	ITEM #	BOX QTY
12-11 x 1	65739ZBN99A	2,500
12-11 x 1-1/2	65742ZBN99A	2,000
12-11 x 2	65744ZBN99A	1,500
12-11 x 2-1/2	65746ZBN99A	1,000

**STRENGTH CHARACTERISTICS**

MINIMUM TORSIONAL	MINIMUM TENSILE	MINIMUM SHEAR
82 in.-lbs.	2197 lbs.	1064 lbs.

**PULL OUT VALUES**

TEST MATERIAL	VALUES
1/2" Plywood	464 lbs.
7/16" OSB	220 lbs.
1" x 6" SYP Grade D	807 lbs.
1" x 6" Douglas Fir	614 lbs.

All test results and recommendations are based on laboratory tests. Specific job site conditions should be taken into consideration when specifying the proper fastener. Actual field values may vary, therefore we assume no liability for use of this information. Pull out values are a measurement of wood material strength. Use of impact style guns for installation not recommended.