

ACCESSORIES

DEKTITE® PREMIUM

More flexible sizing for better coverage



EASY TO IDENTIFY

Dektite brand name engraved on product for traceability

UNIQUE CONE DESIGN

Provides 10mm (1/2") continuous contact with flashed pipe providing a watertight seal

CLEAR MARKINGS

Makes for easier cutting to pipe size

PROVEN DESIGN

Associated with the roofing industry globally for over 40 years

SIZE RANGES - NUMBERS 0-9

Available in Black and Grey EPDM, and Red Silicone

TWENTY YEAR WARRANTY

Just fit it and forget it - we've got you covered

INSTALLATION INSTRUCTIONS

- ≡ Cut Dektite at appropriate pipe diameter marking.
- ≡ Slide Dektite flashing down over pipe.
- ≡ Apply sealant on underside of flexible aluminum base.
- ≡ Press Dektite base into contours of panel configuration.
- ≡ Fasten Dektite to surface with long- life, self drilling fasteners. Apply additional sealant around base if desired.
- ≡ Can be fitted on the 'diamond' for steep roofs and deep corrugations

20 YEAR WARRANTY!

SELECTION GUIDE

BLACK EPDM	GREY EPDM	RED SILICONE	DESCRIPTION	PIPE OD	BASE SIZE	ROOF PITCH	CARTON QTY
DFE10MB	DFE10MG	DFE10MRE	Dektite Premium Micro	0-.75	2.34x2.34	12/12	20
DFE100B	DFE100G	DFE100RE	Dektite Premium #0	0-1.5	4x4	12/12	20
DFE100BS	DFE100GS	DFE100RES	Dektite Prem. #0 Solar	0-1.5	4x4	12/12	20
DFE101B	DFE101G	DFE101RE	Dektite Premium #1	0-2.75	5.5x5.5	12/12	15
DFE101BM			Dektite Prem. Multicable	0-0.25	5.5x5.5	12/12	15
DFE101BS	DFE101GS	DFE101RES	Dektite Prem. #1 Solar	0.25-2.25	5.5x5.5	12/12	15
DFE102B	DFE102G	DFE102RE	Dektite Premium #6	0.25-3	7x7	12/12	15
DFE102BA	DFE102GA	DFE102REA	Dektite Prem. 50-76	2-3	7x7	12/12	15
DFE103B	DFE103G	DFE103RE	Dektite Premium #3	0.25-5	8.75x8.75	12/12	15
DFE104B	DFE104G	DFE104RE	Dektite Premium #4	3-7	11x11	12/12	10
DFE105B	DFE105G	DFE105RE	Dektite Premium #5	4-8	12.25x12.25	10/12	10
DFE106B	DFE106G	DFE106RE	Dektite Premium #6	5-9	14.25x14.25	10/12	10
DFE107B	DFE107G	DFE107RE	Dektite Premium #7	6-12	18x18	10/12	10
DFE108B	DFE108G	DFE108RE	Dektite Premium #8	6.75-14	19.5x19.5	10/12	5
DFE109B	DFE109G	DFE109RE	Dektite Premium #9	9-20	26.75x26.75	10/12	5

Dektite is a registered trademarks of DEKS Industries Pty Ltd. PDM will withstand constant temperatures at the roof line of -58°F to 239°F and up to 302°F intermittently. Red Silicone will withstand constant temperatures at the roof line of -58°F to 392°F and up to 482°F intermittently. Please Note that the outside temperature of the pipe may be significantly different to the exit temperature of the appliance.



Scan here for more product information and to view our entire catalog!

ASHLAND, OH

1628 TROY RD
ASHLAND, OH 44805
(800) 321-6977

FLAT ROCK, NC

161 COMMERCIAL BLVD
FLAT ROCK, NC 28731
(828) 692-2603

HOUSTON, TX

4822 N. SAM HOUSTON PKWY W., STE 100
HOUSTON, TX 77086
(800) 503-2105

ACCESSORIES

DEKTITE® ORIGINAL

The original watertight flashing for metal roof penetrations



EASY TO IDENTIFY

Dektite brand name engraved on product for traceability

UNIQUE CONE DESIGN

Provides 10mm (1/2") continuous contact with flashed pipe providing a watertight seal

CLEAR MARKINGS

Makes for easier cutting to pipe size

PROVEN DESIGN

Associated with the roofing industry globally for over 40 years

SIZE RANGES - NUMBERS 0-9

Available in Black and Grey EPDM, and Red Silicone

TWENTY YEAR WARRANTY

Just fit it and forget it - we've got you covered

INSTALLATION INSTRUCTIONS

- ≡ Cut Dektite at appropriate pipe diameter marking.
- ≡ Slide Dektite flashing down over pipe.
- ≡ Apply sealant on underside of flexible aluminum base.
- ≡ Press Dektite base into contours of panel configuration.
- ≡ Fasten Dektite to surface with long-life, self drilling fasteners. Apply additional sealant around base if desired.

20 YEAR WARRANTY!

SELECTION GUIDE

BLACK EPDM	GREY EPDM	RED SILICONE	DESCRIPTION	PIPE OD	BASE OD	ROOF PITCH	CARTON QTY
DF100B	DF100G	DF200RE	Dektite Original #0	0 - 1.5	3.75	12/12	40
DF101B	DF101G	DF201RE	Dektite Original #1	0.25 - 2.5	34.75	10/12	10
DF102B	DF102G	DF202RE	Dektite Original #2	1.75-3.75	6.5	10/12	10
DF103B	DF103G	DF203RE	Dektite Original #3	0.25 - 5	8	10/12	10
DF104B	DF104G	DF204RE	Dektite Original #4	3 - 6.25	9.5	10/12	10
DF105B	DF105G	DF205RE	Dektite Original #5	4.25 - 7.5	11	10/12	5
DF106B	DF106G	DF206RE	Dektite Original #6	5-9	12.75	10/12	5
DF107B	DF107G	DF207RE	Dektite Original #7	6-11	14.75	10/12	5
DF108B	DF108G	DF208RE	Dektite Original #8	7-13	16.75	10/12	5
DF109B	DF109G	DF209RE	Dektite Original #9	10-19	25.5	10/12	5

Dektite is a registered trademarks of DEKS Industries Pty Ltd. PDM will withstand constant temperatures at the roof line of -58°F to 239°F and up to 302°F intermittently. Red Silicone will withstand constant temperatures at the roof line of -58°F to 392°F and up to 482°F intermittently. Please Note that the outside temperature of the pipe may be significantly different to the exit temperature of the appliance.



Scan here for more product information and to view our entire catalog!

ASHLAND, OH
 1628 TROY RD
 ASHLAND, OH 44805
 (800) 321-6977

FLAT ROCK, NC
 161 COMMERCIAL BLVD
 FLAT ROCK, NC 28731
 (828) 692-2603

HOUSTON, TX
 4822 N. SAM HOUSTON PKWY W., STE 100
 HOUSTON, TX 77086
 (800) 503-2105