

METAL TO WOOD FASTENERS

#14 WOODTITE®



HEAD

1/4" hex head

Wet paint application for consistent socket fit and weathering performance

THREAD

Major Hi Diameter: .194"/.184"
Minor Diameter: .133"/.128"

POINT

Type-17 point

WASHER

Bonded Sealing Washer

MATERIAL

Carbon Steel

FINISH

Zinc Plated with corrosion resistant coating



PRODUCT SUPERIORITY

- ≡ Wet paint application for consistent socket fit and weathering performance
- ≡ Type-17 point helps to penetrate metal more quickly while minimizing chips
- ≡ 26 Degree sharp point for quick piercing
- ≡ Can be painted industry standard colors

AVAILABLE SIZES

SIZE	ITEM #	BOX QTY
14-10 x 1	80613ZBN99ZZHSL	2,500
14-10 x 1-1/2	80001ZBN99ZZHSL	2,000
14-10 x 2	80009ZBN99ZZHSL	1,500
14-10 x 2-1/2	82014ZBN99ZZHSL	1,000
14-10 x 3-1/2	14446ZBN99ZZHSL	500

STRENGTH CHARACTERISTICS

MINIMUM TORSIONAL	MINIMUM TENSILE	MINIMUM SHEAR
125 in. lbs.	3,150 lbs.	2,150 lbs.

All test results and recommendations are based on laboratory tests. Specific job site conditions should be taken into consideration when specifying the proper fastener. Actual field values may vary, therefore we assume no liability for use of this information. Pull out values are a measurement of wood material strength.

Installation Instructions - Do not use impact style guns. Use an electric screw gun with 2,500 RPM max.



Scan here for more product information and to view our entire catalog!

ASHLAND, OH

1628 TROY RD
ASHLAND, OH 44805
(800) 321-6977

FLAT ROCK, NC

161 COMMERCIAL BLVD
FLAT ROCK, NC 28731
(828) 692-2603

HOUSTON, TX

4822 N. SAM HOUSTON PKWY W., STE 100
HOUSTON, TX 77086
(800) 503-2105