

ACCESSORIES

ULTIBOND®

Metal Roof Sealant



EASE OF USE

Fixed nozzle for easy application

Tack-free in less than one hour

DURABLE

Strong adhesion to galvanized, fluoropolymers, aluminum, stainless, laminates, glass, and vinyl

All-weather sealant

Highly mildew resistant

Flexible in low temps

Resistant to heat, cold, water, ozone and UV rays

PRODUCT SUPERIORITY

- ≡ Excellent cohesion strength after cure
- ≡ Available in translucent and industry standard colors
- ≡ Adheres to Aluminum, Steel, Galvalume, Painted Surfaces including Kynar
- ≡ Use for metal roof laps, trim, flashing, roof boots, gutters
- ≡ Made in the USA

Properties	Translucent Neutral Cure Silicone	Color Matched PolyEther
Tack Free Time	Less than 1 hour	Less than 1 hour
ASTM C920	Type S, Grade NS, Class 50 Use A, G, M, O	Type S, Grade NS, Use T, NT, I, G, A
Tensile Strength	341 psi	225 psi
Shear	122 psi	275 psi
Elongation	715%	275%
Service Temperature	-55 to 300 Degrees F	-75 to 300 (Intermittent) Degrees F
UV Resistance	Excellent	Excellent

*Testing substrate compatibility with any sealant before full application is recommended.



Scan here for more product information and to view our entire catalog!

ASHLAND, OH

1628 TROY RD
ASHLAND, OH 44805
(800) 321-6977

FLAT ROCK, NC

161 COMMERCIAL BLVD
FLAT ROCK, NC 28731
(828) 692-2603

HOUSTON, TX

4822 N. SAM HOUSTON PKWY W., STE 100
HOUSTON, TX 77086
(800) 503-2105